

## 3C



## 3CX



## 3CX SM



## 3CX SUPER



## 3CX SUPER SM



## 3CX CONTRACTOR



Operating weight	kg	6490 / 6630	7370	8070	7725	8425	8070
Gross engine power	hp (kW)	85 (63)	85 (63)	92 (68.6)	92 (68.6)	92 (68.6)	100 (74.2)
Dig depth ret/ext	m	4.42 / 5.44	4.24	4.25 / 5.46	4.37	4.37 / 5.58	4.24 / 5.46
Steer mode		2WS	2WS	2WS	WS	4WS	2WS
Loader shovel breakout	kgf	5322	6170	6531	6227	6590	6531
Loader shovel capacity	m <sup>3</sup>	1.25	1.0	1.0	1.0	1.0	1.0
Maximum dipper tearout	kgf	3175	3217	2255 / 3225	3217	2255 / 3225	2729 / 3903
Maximum bucket tearout	kgf	5202	6324	6228	6324	6228	6228
Optimum pump flow*	l/min	90	154	154	154	154	165

\* Pump size may vary by territory

## 4CX



## 4CX SM



## 4CX SUPER



## 4CX SUPER SM



## 4CN



Operating weight	kg	7950	8660	8130	8880	8660
Gross engine power	hp (kW)	100 (74.2)	100 (74.2)	100 (74.2)	100 (74.2)	100 (74.2)
Dig depth ret/ext	m	4.32	4.32 / 5.53	4.98	4.98 / 6.14	5.191
Steer mode		4WS	4WS	4WS	4WS	4WS
Loader shovel breakout	kgf	6227	6590	6590	6590	6590
Loader shovel capacity	m <sup>3</sup>	1.1	1.2	1.3	1.3	1.3
Maximum dipper tearout	kgf	3893	2729 / 3903	3713	2675 / 3722	3893
Maximum bucket tearout	kgf	6228	6228	6228	6228	6929
Optimum pump flow*	l/min	165	165	165	165	165