Bobcat®

TRENCHER

ATTACHMENTS

TRENCHER

Features

Cost-effective, versatile trenching!

Trenchers that really dig their work!

Tackle tough trenching jobs with one of four Bobcat trencher attachments. The LT112, LT213, LT313 and LT405 are designed and built specifically for Bobcat loaders. That means reliable, cost-effective production as well as Bobcat warranty, parts and service support.

With 60 cm and 90 cm (optional) dig depths, the LT112 and LT213 are ideal for light-to-medium trenching jobs. The LT313, with its 90 cm or 120 cm (optional) dig depth, can easily handle medium-to-high production trenching. The LT112, LT213 and LT313 models feature manual side-shift with an optional hydraulic side-shift available on the LT213 and LT313. The LT405, with a 1.2 m or 1.5 m (optional) dig depth, is a high-production trencher for use on Bobcat loaders with high-flow capability

Specifications

Trencher	LT112 (60 cm)	LT213 (90 cm)	LT313 (90-120 cm)	LT405 (120-150 cm)
Features	Manual side-shift***	Manual side-shift***	Manual side-shift***	Hydraulic side-shift
	42 mm chain	42 mm chain , ABF chain (51 mm)	Double standard, ABF chain (51 mm)	Double standard, ABF chain (51 mm)
	305 mm dia. single removable auger	305 mm dia. single removable auger	365 mm dia. single removable auger	305 mm dia. dual removable augers
	Grease cylinder chain tightener	Grease cylinder chain tightener	Grease cylinder chain tightener	Grease cylinder chain tightener
	Chain options available	Chain options available	Chain options available	Chain options available
	Trench cleaner	Trench cleaner	Trench cleaner	Trench cleaner
Operating Weight*	279 kg	329 kg	433 kg	689 kg
Trenching Widths Available	102 - 203 mm	102 - 203 mm	152 - 305 mm	152 - 305 mm
Flow Range	30–57 l/min	42–68 l/min	57–121 l/min	79 l/min
Maximum Operating Pressure	20684 kPa	20684 kPa	20684 kPa	22753 kPa
Approved Bobcat Loaders	463, MT52	**553, S130, T140 TOOLCAT	S130, S150, S160, S175, S185, S205, S220, S250, S300, A300, T140, T180, T190, T250, T300	S175H, S185H, S205H, S220H, S250H, S300H, A300H, T180H, T190H, T250H, T300H
A. Overall Length	1542 mm	1880 mm	2019 mm	2667 mm
B. Std. Boom Length	1000 mm	1334 mm	1410 mm	1600 mm
C. Dig Depth	610 mm	915 mm	915-1218 mm	1218–1524 mm
D. Frame Width	915 mm	1422 mm	1422 mm	1651 mm
E. Side-Shift Travel	409 mm	***587 mm	***587 mm	660 mm
F. Auger Clearance	351–401 mm	351–401 mm	607–686 mm	483 mm





* Without teeth

** When using the LT213 trencher on a 553, limit use to easy trenching conditions with a 152 mm maximum trench width.

*** LT213/LT313 side-shifts to the right. Optional hydraulic side-shift available.

BOBCAT EUROPE
J. Huysmanslaan, 59
B - 1651 LOT Belgium
www.bobcat.com
An Ingersoll-Rand business

Specifications and design are subject to change without notice.

4453240-EN (07-2005)